

## UL Fuse Classification

UL Class	Fuse Overload Characteristics	Interrupting Rating, Amperes	AC Voltage Rating	Available Ampere Ratings	Ferraz-Shawmut Part Number
L	TIME-DELAY	200,000	600	200 - 6000	A4BQ
				601 - 4000	A4BT
RK1***	TIME-DELAY	200,000	250	1/10 - 600	A2D-R
			600		A6D-R
	FAST-ACTING	200,000	250	1 - 600	A2K-R
			600		A6K-R
RK5	TIME-DELAY	200,000	250	1/10 - 600	TR-R
			600		A2D-R
					TRS-R
					A6D-R
					A6DR IDSR
T	FAST-ACTING	200,000	300	1 - 1200	A3T
			600	1 - 1200	A6T
J	TIME-DELAY	200,000	600	1 - 600	AJT
	FAST-ACTING	200,000	600	1 - 600	A4J
CC	TIME-DELAY	200,000	600	1/10 - 30	ATQR
				1/4 - 30	ATDR
	FAST-ACTING	200,000	600	1/10	ATMR
CD	TIME-DELAY	200,000	600	35 - 60	ATDR
G	TIME-DELAY	100,000	480	1/2 - 60	AG
K5	FAST-ACTING	50,000	250	1 - 600	OT
			600		OTS
H	Renewable Fuses				